

Hotmarker SP Series Table setting parameters

FIELD	DESCRIPTION	OPTIONS / RANGE
TABLE	Table number	1 – 20
INDEX	Comment of the Table	Max. 5 digits of ASCII character
WORK	Work mode	0-4 0:TUBE 1:LABEL 2:BOARD 3: BRD-L 4:OPTION(invalid for SP8600)
CHAR ID	Type of font	0-17
DIR	Printing direction	0 / 1 0:PAR (parallel) 1:CRS (cross)
Phor	Horizontal character pitch	1.0 – 9.9 mm
Pver	Vertical character pitch	1 – 99 dots
C.POS	Cutter position	50.0 – 100.0 mm
F.ADJ	Adjustment of feeding Rate	80.0 – 120.0 %
Y-ADJ	Vertical adjustment of marking position	50 – 350 dots
Y-Max	Maximum marking width	40 – 160 dots
LENGTH	Print length	0 – 999.9 mm
NOG	Type of numbering	0 / 1 0:Decimal 1:Hexadecimal
ESP	Front blank space	0.1 – 99.9 mm
R.SP	Rear blank space	0.1 – 99.9 mm
DENSITY	Marking density	50 – 220 units
RPT	Repeat mode	0 / 1 0:Per area 1:Per line
LABEL	Positioning of Marker Labels of precut type	1.0 – 50.0 mm
T.CUT	Adjustment of tube feeding rate at tube cutter function	80.0 – 120.0 %

FIELD	DESCRIPTION	OPTIONS / RANGE
CUT	Mode of cutting	0-3 0:NO CUT 1:PART 2:COMPL 3:SET MODE
PAIR	Number of pieces between complete cuts	2-3 2:2pieces 3:3pieces